

KST A12-T V8.0 2.0N.m@8.4 Volt Softstart



Artikelnummer: KST-1015

KST A12-T V8.0 2.0N.m@8.4 Volt Softstart

Hersteller: KST

Produktinformationen "KST A12-T V8.0 2.0N.m@8.4 Volt Softstart";

KST A12-T Technische Details:

Signal: PWM
Rated Voltage: DC7.4V
Voltage Range: DC6.0V-8.4V
Stalling Torque: 1.6N.m@6.0V
1.8N.m@7.4V
2.0N.m@8.4V
Speed 0.15sec/60deg;@6.0V
0.13sec/60deg;@7.4V
0.12sec/60deg;@8.4V
Working Frequency: 1520us/333Hz
Default Travel Angle: $\pm 60^\circ$; = 120° ; Total
Temperature Range: -10°C ; \dots ; $+60^\circ\text{C}$
Soft Start: Yes
Programmable: Yes
Case Material: Aluminum Alloy
Motor Type; 7 Phases Coreless DC Motor
Gear Set Material: Hardened Steel
Position Sensor: Contactless
Case Dimensions: 30mm*12mm*35.5mm \pm 0.2mm
Weight: 32g \pm 10%

Programmierbar mit KST-Tool 1

Verfügbare Downloads:

Download
KST_1015_A12_T_V8_Datenblatt_02_2022_de.pdf

Download
KST_1015_A12_TV8_0EU_Konformitaetserklaerung.PDF

Preis: 79,90 EUR [inkl. 19% MwSt zzgl. Versandkosten]