

KST X22-7.4-M-860-1 V8.0 HLS 7.0N.m@7.4 Volt



Artikelnummer: KST-0411

KST X22-7.4-M-860-1 V8.0 HLS 7.0N.m@7.4 Volt

Hersteller: KST

Produktinformationen "KST X22-7.4-M-860-1 V8.0 HLS 7.0N.m@7.4 Volt";

X22-7.4-M-860-1 HLS / PWM

Operating Data:

Signal: PWM

Rated Voltage: DC7.4V

Voltage Range: DC6.0V-8.4V

Stalling Torque: 7.0N.m@7.4V

Rated Torque: 2.2N.m@7.4V

Stalling Current: 7.50 A

Rated Current: 1.98

No load Speed: 0.15sec/60deg;@7.4V

Rated Speed 0.21sec/60deg;@7.4V

Working Frequency: 1500us/333Hz

Devault Travel Angel: +/- 100deg;= 200deg; Total when 500-2500 us

Temperature Range: -10deg;C - +65deg;C

Programmable: Yes

Soft start: Programmable

Case Material: Aluminum Alloy

Motor Type: Brushless DC Motor

Gear Set Material: Hardened Steel

Position Sensor: Contactless

Output Shaft: 25T-8

Case Dimensions: 45mm*22mm*52mm±0.2mm

Weight: 128g±10%

Ball Bearing: 6 BB

Programmierbar mit KST-Tool #1

Bitte beachten Sie die Servo-Spezifikation des Modell Herstellers bei der Auswahl der Servos.

Verfügbare Downloads:

Download

KST_0411_X22_7_4_M_860EU_Konformitaetserklaerung.PDF

Download

KST_0411_X22_XX_M_860_X_Datenblatt_12_2021_de_.pdf

Download KST_0411_X22_7_4_M_860_STEP.zip

RC-Bereich/Sender/Servos/Elektronik > Servos > KST > KST 21mm Servos > KST X22-7.4-M-860-1 V8.0 HLS 7.0N.m@

KST X22-7.4-M-860-1 V8.0 HLS 7.0N.m@7.4 Volt

Preis: 269,00 EUR [inkl. 19% MwSt zzgl. Versandkosten]

Im Shop aufgenommen am Dienstag, 13. Juni 2023