T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .



Artikelnummer: FP05003241-3

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

Hersteller: Futaba - minicars

Product Info:

This is a promotion version of the T26SZ radio that includes three R7214SB receivers!

The long-awaited successor to the best-selling model “T18SZ”, the new T26SZ is now official!
The new T26SZ is positioned in between the highly desirable high-end T32MZ-WC series that is loved by many competitors and the mid-range T16IZ-Super. For pilots who fly anything and everything, demand unquestioned reliability and seek a future-proof radio that offers the highest level of programming sophistication, Futaba’s T26SZ will be impossible to ignore. With its user-friendly interface, twin screens, silky-smooth hall effect non-contact gimbals, near like-for-like T32MZ feature set, elegant styling and latest FASSTest 26ch protocol, the T26SZ is highly likely to tick every box on your extensive wish list. It is a masterpiece that is comparable to the high-end class, and can be said to be the result of Futaba's many years of accumulated know-how and solid results.

S.BUS2 SYSTEM
Multiple servos, gyros and telemetry sensors can be easily installed with a minimum of cables.

MAIN LCD COLOR DISPLAY
HVGA 4.3" full color backlit LCD transflective (indoor / outdoor visible) touch screen.

SECONDARY LCD DISPLAY
A high quality reflective LCD for easy recognition of telemetry information.

SD CARD PORT
Update software, store model data and upload picture files using the microSD port.

HIGH CAPACITY LI-PO
2100mAh offers a comfortable operating duration and real peace of mind.

INTUITIVE PROGRAMMING
Model-specific programming and editing has never been easier.

MULTIPROP CHANNEL EXPANSION
Using the MPDX-1 multiprop decoder (sold separately) one channel can be divided into eight channels. Two MPDX-1s

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

can be used.

FEELS GOOD
Magnetic detection non-contact potentiometers offer fine, ultra-precise, long-lasting operation. A throttle stick external adjustment screw allows ratchet or self-neutralizing spring adjustment.

SWITCH REPLACEMENT
Change four of the toggles on the right and left shoulder with your chosen two-position, three-position or momentary switch.

Features:

ï¿½
The T26SZ transmitter is changable to either Mode-1 or Mode-2 in the software. See the manual for more info.
ï¿½
FASSTest26, FASSTest18, FASSTest12, S-FHSS & T-FHSS protocols
ï¿½
26 channels (24+2)
ï¿½
Full color 4.3 inch touch screen
ï¿½
3.0" LCD sub display
ï¿½
High quality finish
ï¿½
Model image display
ï¿½
Smooth non-contact stick potentiometer
ï¿½
Shoulder switch upgrade / replacement
ï¿½
Four rear sliders (paired)
ï¿½
Vibration alert
ï¿½
Voice function
ï¿½
Telemetry system
ï¿½
Four stick modes (1-4)
ï¿½
MicroSD card software update
ï¿½
High capacity LiPo
ï¿½
USB-C charging
ï¿½
Earphone jack
ï¿½
Calendar clock

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

ï¿½
S.BUS I/F enabled
ï¿½
Wireless trainer system
ï¿½
±240 step sub trim
ï¿½
Sub trim balance
ï¿½
DLPH-2 settings
ï¿½
Receiver mode-setting port
ï¿½
Gyro setting for CGY755 / 760R / 770R / GYA553
ï¿½
8 flight conditions
ï¿½
30 pre-programmed mixers
ï¿½
10 free programmable mixers
ï¿½
Retract and door sequencer
ï¿½
13 fixed-wing types
ï¿½
3 fixed-wing tail types
ï¿½
2 fixed-wing rudder types
ï¿½
8 helicopter swash types
ï¿½
Supports 14 telemetry sensor types
ï¿½
GPS enabled

Key Programming Features (for full list see manual):

ï¿½
Model name (15 characters)
ï¿½
Sub trim
ï¿½
Sub trim balance
ï¿½
Servo reverse
ï¿½
Fail-safe
ï¿½
Exponential
ï¿½
Throttle cut
ï¿½
End point / ATV (30 - 140%)
ï¿½

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

Servo speed
ï¿½
Trainer function
ï¿½
Servo monitor
ï¿½
Trim setting (step, rate, mode)
ï¿½
Data editor (for S.Bus equipment)
ï¿½
10 programmable mixers
ï¿½
30 pre-programmed mixers
ï¿½
Aileron differential
ï¿½
Air brake
ï¿½
Flap trim
ï¿½
Flap setting
ï¿½
Butterfly
ï¿½
Camber mix
ï¿½
Camber flap-elevator
ï¿½
Elevator to camber
ï¿½
Aileron to camber flap
ï¿½
Aileron to rudder
ï¿½
V tail
ï¿½
Ailvator
ï¿½
Winglet
ï¿½
Aileron to brake flap
ï¿½
Snap roll
ï¿½
Servo monitor
ï¿½
Twin timers
ï¿½
Stick alarm
ï¿½
Battery fail-safe
ï¿½
Gyro sense
ï¿½
Multi engine

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

ï¿½
Motor mix
ï¿½
Condition name
ï¿½
AFR (dual rate)
ï¿½
AFR (curve mode)
ï¿½
AFR curve point number (17 points)
ï¿½
Logic switch (condition switch only)
ï¿½
Acceleration mixing
ï¿½
Pitch curve / pitch trim
ï¿½
Throttle curve / throttle hover trim
ï¿½
Pitch to needle mix
ï¿½
Revolution mix
ï¿½
Swash ring
ï¿½
Idle down
ï¿½
Throttle limiter
ï¿½
Swash setting
ï¿½
Swash AFR
ï¿½
System timer
ï¿½
Function setting
ï¿½
Governor

Telemetry functions:

ï¿½
Temperature
ï¿½
RPM (magnetic & optic)
ï¿½
Altitude
ï¿½
GPS
ï¿½
Voltage
ï¿½
Receiver battery
ï¿½

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

Current
ï¿½
Data logging

What's in the Box:

ï¿½
T26SZ 26-channel transmitter
ï¿½
3x R7214SB receivers
ï¿½
7.4V 2000mAh Li-Po Tx battery pack
ï¿½
USB-C charge lead
ï¿½
Neck strap
ï¿½
Tool set
ï¿½
Short manual (full pdf manual as download)

Produktinfo:

Dies ist eine Werbeversion des T26SZ-Radios, die drei R7214SB Empfï¿½nger enthï¿½lt!

Der lang erwartete Nachfolger des meistverkauften Modells "T18SZ", der neue T26SZ, ist nun offiziell!
Der neue T26SZ befindet sich zwischen der sehr begehrten High-End-Serie T32MZ-WC, die von vielen Wettbewerbern geliebt wird, und dem Mittelklassemodell T16IZ-Super. Fï¿½r Piloten, die alles fliegen, uneingeschrï¿½nkte Zuverlï¿½ssigkeit fordern und ein zukunftssicheres Radio mit hï¿½chster Programmqualitï¿½t suchen, wird Futabas T26SZ unmï¿½glich zu ignorieren sein. Mit seiner benutzerfreundlichen Oberflï¿½che, den zwei Bildschirmen, den seidig-glatten Hall-Effekt berï¿½hrungslosen Gimbals, dem nahezu gleichwertigen T32MZ-Funktionsset, dem eleganten Design und dem neuesten FASSTest 26-Kanal-Protokoll wird der T26SZ mit hoher Wahrscheinlichkeit jedes Kriterium auf Ihrer umfangreichen Wunschliste erfï¿½llen. Es ist ein Meisterwerk, das mit der High-End-Klasse vergleichbar ist und als Ergebnis von Futabas jahrelangem erworbenem Know-how und soliden Ergebnissen angesehen werden kann.

S.BUS2 SYSTEM
Mehrere Servos, Gyros und Telemetriesensoren kï¿½nnen mit minimalem Kabelaufwand leicht installiert werden.

HAUPT-LCD-FARBDISPLAY
HVGA 4,3" vollfarbiger LCD-Touchscreen mit

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

transflectiver (innen / drauï¿½en sichtbar) Touchscreen.

SEKUNDï¿½RES LCD-DISPLAY
Ein hochwertiges reflektierendes LCD zur einfachen Erkennung von Telemetrieinformationen.

SD-KARTENPORT
Software aktualisieren, Modelldaten speichern und Bilddateien ï¿½ber den microSD-Port hochladen.

HOCHKAPAZITï¿½T LI-PO
2100mAh bietet eine komfortable Betriebsdauer und echtes Vertrauen.

INTUITIVE PROGRAMMIERUNG
Modellspezifische Programmierung und Bearbeitung war noch nie einfacher.

MULTIPROP-KANALERWEITERUNG
Mit dem MPDX-1 Multiprop-Decoder (separat erhï¿½ltlich) kann ein Kanal in acht Kanï¿½le unterteilt werden. Zwei MPDX-1 kï¿½nnen verwendet werden.

Fï¿½HLT SICH GUT AN
Magnetische Erkennungs-kontaktlose Potentiometer bieten einen feinen, ultraprï¿½zisen und langanhaltenden Betrieb. Eine externe Einstellschraube des Gashebels ermï¿½glicht eine Ratschen- oder Selbstneutralisierungsfeder.

SCHALTERWECHSEL
Wechseln Sie vier der Schalter auf der rechten und linken Schulter mit Ihrem gewï¿½hlten Zwei-, Drei-Positionen- oder Momentschalter.

Merkmale:

Der T26SZ-Sender kann in der Software entweder auf Modus-1 oder Modus-2 umgestellt werden. Weitere Informationen finden Sie im Handbuch.
FASSTest26, FASSTest18, FASSTest12, S-FHSS & T-FHSS Protokolle
26 Kanï¿½le (24+2)
Vollfarbiger 4,3-Zoll-Touchscreen
3,0" LCD-Subdisplay
Hochwertige Oberflï¿½che
Modellbilddisplay
Glattes, berï¿½hrungsloses Stick-Potentiometer
Schulterschalter-Upgrade / Austausch
Vier hintere Schieberegler (gepaart)
Vibrationswarnung
Sprachfunktion
Telemetriesystem
Vier Stick-Modi (1-4)
MicroSD-Karten-Software-Update

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

Hochleistungs-LiPo
USB-C Ladeanschluss
Kopfhï¿½rerbuchse
Kalenderuhr
S.BUS I/F aktiviert
Kabelloses Trainersystem
±240 Stufen Subtrim
Subtrim-Balance
DLPH-2-Einstellungen
Empfï¿½nger-Moduseinstellung
Gyro-Einstellung fï¿½r CGY755 / 760R / 770R / GYA553
8 Flugbedingungen
30 vorprogrammierte Mischer
10 frei programmierbare Mischer
Einfahr- und Tï¿½rsequenzer
13 Starrflï¿½geltypen
3 Starrflï¿½gel-Hecktypen
2 Starrflï¿½gel-Seitenrudertypen
8 Hubschrauberschwung Typen
Unterstï¿½tzt 14 Telemetriesensortypen
GPS-aktiviert

Wichtige Programmierungsfunktionen (vollstï¿½ndige Liste siehe Handbuch):

Modellname (15 Zeichen)
Subtrim
Subtrim-Balance
Servo-Reverse
Fail-safe
Exponentiell
Drosselschnitt
Endpunkt / ATV (30 - 140%)
Servogeschwindigkeit
Trainerfunktion
Servomonitor
Trimmeinstellung (Schritt, Rate, Modus)
Dateneditor (fï¿½r S.Bus-Gerï¿½te)
10 programmierbare Mischer
30 vorprogrammiert Mischer
Querruder-Differential
Luftbremse
Klappentrimmung
Klappeneinstellung
Schmetterling
Sturzmischung
Camber-Klappen-Hï¿½henruder
Hï¿½henruder an Sturz
Querruder zu Sturmklappe
Querruder zu Seitenruder
V-Heck
Ailvator
Flï¿½gelstï¿½ck
Querruder zu Bremsklappe

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

Snap-Roll
Servomonitor
Doppeltimer
Stockalarm
Batterie-Sicherheitsmechanismus
Gyro-Sensor
Mehrmotor-Mix
Motormischung
Statusbezeichnung
AFR (Doppelrate)
AFR (Kurvenmodus)
AFR-Kurvenpunktnummer (17 Punkte)
Logikschalter (nur Zustandsschalter)
Beschleunigungsmischung
Nickkurve / Nickschnitttrimm
Drosselkurve / Drossel-Hover-Trim
Nick-zu-Nadel-Mix
Umdrehungsmischung
Schwungring
Leerlauf runter
Gasbegrenzer
Schwungschwung
Schwung-AFR
Systemtimer
Funktionseinstellung
Regulator

Telemetriefunktionen:

Temperatur
Drehzahl (magnetisch & optisch)
Hï¿½he
GPS
Spannung
Empfï¿½ngerbatterie
Strom
Datenerfassung

Was ist in der Box:

T26SZ 26-Kanal-Sender
3x R7214SB Empfï¿½nger
7,4V 2000mAh Li-Po Tx Akkupack
USB-C-Ladekabel
Halsgurt
Werkzeugset
Kurzes Handbuch (vollstï¿½ndiges PDF-Handbuch als Download)

Preis: 1.245,00 EUR [inkl. 19% MwSt zzgl. Versandkosten]

T26SZ Radio FASSTest26, 3/R7214SB, 2S LiPo .

Im Shop aufgenommen am Mittwoch, 04. Februar 2026

ABC-RCModellbau